Government of Maharashtra

SEAC-III2014/C.R.122/TC-3 Environment department Room No. 217, 2nd floor, Mantralaya Annexe, Mumbai- 400 032. Dated: 23rd February, 2015

To, M/s. Kate Jagtap Associates S.No.38/2/1,M.S. Kate chowk, Pimple Guray, Pune

Subject: Environment clearance for Proposed residential Project "Bselio" at S.No.38/2/1 at Village. Pimple Gurav, Tal. Haveli, Distt. Pune by M/s.Kate Jagtap Associates

Sir.

This has reference to your communication on the above mentioned subject. The proposal was considered as per the EIA Notification - 2006, by the State Level Expert Appraisal Committee-III, Maharashtra in its 22nd meeting and recommend the project for prior environmental clearance to SEIAA. Information submitted by you has been considered by State Level Environment Impact Assessment Authority in its 80th meeting.

2. It is noted that the proposal is considered by SEAC-III under screening category 8(a) B2 as per EIA Notification 2006.

Brief Information of the project submitted by Project Proponent is as-

Name of Project	"Basileo"
Project Proponent	M/s. Kate Jagtap Associates
Consultant	M/s. Ultra-Tech Environmental Consultancy & Laboratory
Type of project: Housing project / Industrial Estate /SRA scheme / MHADA / Township or others	Residential and Commercial Development.
Location of the project	S.No.38/2/1 M.S. Kate chowk, at Pimple Gurav, Tal- Haveli, DistPune, State - Maharashtra
Whether in Corporation / Municipal / other area	Pimpri Chinchwad Municipal Corporation
Applicability of the DCR	Pimpri Chinchwad Municipal Corporation
IOD/IOA/Concession document or any other form	Received.

	1					
of document as						
applicable(Clarifying its						
conformity with local						
planning rules & provision)						
Note on the initiated work	No work has been initiated as per sanction obtained.					
(If applicable)	-					
LOI/NOC from MHADA	N.A					
/ Other approvals (If						
applicable)						
Total Plot Area (sq.	Total Plot Area: : 52, 2	56.65 m ²				
m.)Deductions	Deduction (For under ro		84.74 m^2			
Net Plot area	Net Plot area: 49, 271.9					
Permissible FSI (including	Total Permissible FSI:-	***************************************				
TDR etc.)		00030000 111				
Proposed Built-up Area	FSI : 68528.88	m ²				
(FSI & Non-FSI)	Non FSI : 63728. 93					
1	Total : 1, 32, 257.8					
Ground-coverage	27, 063.14 (54.92 % of					
Percentage (%)	2.,000.11(07.72 7001	not prot area;				
(Note: Percentage of plot	The state of the s					
not open to sky)						
Estimated cost of the	Rs. 282 Cr. /-					
project	RS. 202 Cl. /-					
No. of building & its						
_	T	>1 CG				
configuration(s)	Туре	No. of floor				
2 ·	<u>A</u>	L.P.+ U.P.+				
ontonera are	В	L.P.+ U.P.+				
	С	L.P.+ U.P.+				
references.	D	L.P.+ U.P.+				
•	E	L.P.+ U.P.+	12			
	F	L.P.+ U.P.+	12			
i I	G	L.P.+ U.P.+	12			
	H	L.P.+ U.P.+	12			
	I	L.P.+ U.P.+	12			
	Commercial I	P+ 3				
	Commercial 2	B+ G+ 6				
	Amenity School 1	Ground				
	Amenity School 2	Ground				
Number of tenements and	Total no. of Tenement					
shops	No. of shops: 8 Nos.	5. 130 NOS.				
	No. of offices: 106					
Terrocorane	No. of Classrooms: 15					
Number of expected	<u> </u>	aidanea - Pina 1	2700			
residents / users	Number of expected re- Floating- 2303	sidents :- Fixed -	3090			
Tenement density per	150 Tenement per hec	for				
hector	130 renement her nec	IOF				
Height of the building(s)	Sr. No. Details		Height of Bldg.(m)			
	1 Residential		42.10			
	2 Commercial 1		12.05			
***************************************	3 Commercial 2		24.05			
	4 Amenity School 1 3.5					
	-2-					
	-four					

	5 Amenity School 2 3.5
	4. Club House 3.5
Right of way (Width of	
the road from the nearest	18 m wide road abutting to the project site
fire station to the	
proposed building(s))	
Turning radius for easy	Turning 9 m radius for easy access of fire tender movement from all
access of fire tender	around the building is 6 m.
movement from all around	
the building excluding the	
width for the plantation	
Existing structure(s)	Temporary structure as permitted by PCMC
Details of the demolition	No demolition work.
with disposal (If applicable)	
Total Water Requirement	Residential
	Dry season:
	• Fresh water (m ³ /day):418
	Source: PCMC
	• Recycled water (m ³ /day):Gardening: 40
	 Recycled water (m³/ day):Flushing: 167
	HVAC makeup: NA
	• Total Fresh Water Requirement (m³/ day): 418
	• Excess treated water(m³/day): 256
	• Club house (m³/ day): 5
	• Swimming Pool (m³/ day):10
	• Fire fighting: - 300 m ³
	Wet Season:
	• Fresh water (m ³ /day): 418
	• Recycled water (m³/ day) Gardening: NA
	• Recycled water (m³/day) Flushing: 167
	HVAC makeup: NA
	● Total Fresh Water Requirement (CMD):418
	• Excess treated water(m³/day): 296
	• Swimming pool(m³/ day): 10
	• Fire fighting (m ³ /day): 300 m ³
	Commercial
	Dry season:
	• Fresh water (m³/day): 83
	• Recycled water (m³/day):Gardening: NA
	• Recycled water (m ³ / day):Flushing: 116
	HVAC makeup: NA
	• Total Fresh Water Requirement (m ³ /day):83
	• Excess treated water(m³/day): 17
	• Swimming Pool (m ³ /day) –NA
	• Club house (m³/day): 5
	• Fire fighting (m³/ day): UGT- 300
	Wet Season:
	• Fresh water (m ³ / day): 83
	• Recycled water (m ³ /day) Gardening: NA
	• Recycled water (m³/ day) Flushing: 116

	a ITY/A C and a NIA
	• HVAC makeup: NA
	• Total Fresh Water Requirement (m³/day):83
	• Excess treated water(m ³ /day): 17
	• Swimming pool(m³/day): NA
	• Fire fighting: -300 m ³
Details about Swimming	• Dimension of Swimming rool: 7.5 m X 16.53 m
Pool:	• Total water Requirement in KLD: 125
	 Water requirement for make up in KLD: 5.6
	 Details of Plant & Machinery used for treatment of Swimming
	pool water: Annexure 1
	 Details of quality to be achieved for swimming pool water and
	parameters to be monitored: Annexure 1
Rain Water Harvesting	Size and no of RWH tank(s) and Quantity:- NA
(RWH)	• Location of the RWH tank(s):- NA
	• Size, no of recharge bore ts and Quantity: - 29 Nos. of RWH
	pits with Bore
	Budgetary allocation (Capital cost and O&M cost)
	Capital Cost: - Rs. 27 lacs
	O & M cost:- Rs. 0.90 lacs/ annum
UGT tanks	Locations of the UGT tanks; -
	Raw water Storage tank Capacity:50 m ³
	Treated water tank Capacity: 501 m ³
	Recycled UG tank Capacity: 283 m ³
	Fire UG tank Capacity: 300 n
Storm water drainage	Natural water drainage pattern- Sloping from North to South
	• Quantity of storm water- 34.62 m³/min
	Size of SWD- 400 mm dia having slope 1:150
Sewage and Waste	• Sewage generation :- Total 530 m ³ /day
water	 Capacity of STP (CMD):- 562 m³
	STP technology:- MBBR
	* Location of the STP: -
	• Area –158 m ²
	 DG sets (during emergency):- Load considered in the Common
	D.G. Set
	Budgetary allocation (Capital cost and O&M cost)
	• Capital Cost: - Rs. 70 lacs
	• O & M cost: - Rs. 30 lacs/ annum
Solid waste Management	Waste generation in the Pre Construction and Construction
_	phase:
	• Quantity of the top soil to be preserved: - 9855 m ³
	proserved, 19655 m
	Disposal of the construction way debris: - This material shall be used
	for back filling and leveling of the plot and remaining will be
	disposed to authorized sites
	Waste generation in the operation Phase:
	• Non-Biodegradable (Kg/day):- 671
	Biodegradable (Kg/day): - 1570
	* E – waste (Kg/month) :- N.A
	* Hazardous waste (Kaymonth) : N.A
	Trazardous wasic (Kg/monin) :- Negligible
	Biomedical waste (Kg/month) (If applicable) :- N.A

STP Sludge (Dry sludge) (Kg/day):- Kg/day approx.

Mode of Disposal of waste:

- Dry waste:- handed over to authorized recyclers
- Wet waste:- handed over to authorized recyclers
- E waste:- N.A
- Hazardous waste:NA
- Biomedical waste (If applicable):- N.A
- STP Sludge (Dry sludge):- 58 kg/ day used as manure

Area requirement:

1. Location of OWC:- Not required

Budgetary allocation (Capital cost and O&M cost)

Capital Cost: Not required O & M cost: Not required

Green Belt Development RG area on ground: 5734.46 RG area on podium: 978.44

Number and list of trees species to be planted in the ground RG:-672

List of Trees:-

3. Plantation:

Botanical Name	Common name	Charecteristics		
Swietenia mahagoni-	Mahogany	Large, semi-evergreen tree forms a loose, rounded canopy and casts light, dappled shade		
Millingtonia hortensis	Indian cork tree	Deciduous, flowering, large tree,	120	
Kigelia pinnata	Sausage tree	Fragrant, nectar-rich flowers attract bats, insects and sunbirds	88	
Albizia lebbeck	Shirish	Deciduous, Tree with dense shade	73	
Peltophorum pterocarpum	Peltophorum	Deciduous, fast growing tree	88	
Anthocephalus cadamba	Kadamb	Evergreen, shady large tree with spreading branches		
Mimusops elengi	Bakul	Rounded canopy, branching low with dense and dark green foliage		
Bauhinia blakeana	Hong Kong Orchid Tree	Semi- deciduous, fast growing tree	19	
Cassia nodosa	Pink Shower Tree	Shady and ornamental tree.	8	
Cordia sebestena	Geiger Tree	Evergreen, flowering tree,	24	
Cassia fistula	Golden Shower tree	Deciduous, Shady Tree		
Saraca indica	Sita Ashok	Garden Tree	6	
Putranjiva roxburghii	Putranjiva	Tree used for Boundary plantation	3	

Thespesia populnea	Portia Tree	Shady Tree	14
Azadirachta indica	Neem	Medicinal Plant, Shady Tree	8
Michelia champaca	Chapha	Strongly fra cant yellow or white flowers.	7
Terminalia catappa	Badam	tall deciduous and erect tree.	4
Total			672

Number and list of trees species to be planted around the border of nallah / stream / pond (If any):- No

• Number, size, age and species of trees to be cut, trees to be transplanted:- --

Nos. of existing tree- Nil

No. of Trees to be retained: NA

No. of trees to be cut- NA

No. of trees to be transplanted- NA.

 NOC for the Tree cutting / transplantation- NA compensatory plantation, if any :- NA

4. Budgetary allocation (Capital cost and O&M cost)

Capital Cost: - Rs. 186.94 Lacs
O & M cost: - Rs. 22.43 lacs/ annum

En	er	gу
----	----	----

Power Supply:

- Residential Connected Load- 3152 kW
 Maximum Demand 1891.2 kVA
- Commercial- Connected Load- 2851 kW
 Maximum Demand 1710 kVA
- Source MSEDCL
 - High efficiency Transformer to reduce losses. Losses for Transformer will be as per IS standards & ECBC norms.

Following are the Energy efficient fixtures would be used in our project for energy conservation:-

- Using automatic timer operation against manual operation for external & common lighting
- Using T5 fixture with electronic ballast against T8. FTL fixture with electromagnet ballast all building
- Using high efficient transformer against conventional transformer
- Solar water heating for minimum 20% design capacity
- % saving --

• Compliance of the ECB(guideline(YES/NO) (If yes then submit compliance in tabular

Sr no	Section No	ECBC requirements	Percentage saving/annum
The state of the s	7.2.1.4	Using automatic timer operation against manual operation for external & common lighting	50%

		1		oina Ts f	vturo	ız/i+h		1	29%
				Using T5 fixture with electronic ballast against T8.				1	ム プ70
	2	2 7.3	1	FTL fixture with					
			el	ectromag	net bal	llast a	.11		
			bu	ilding					
		3 8.2.1.1 Using high efficient transformer against conventional transformer						2%	
	3								
					r heating for				
	2	6.	1	inimum 2		_			
			ł	pacity					
			allocation(ost &	0& N	И Со	ost)	
			st – Rs.30						
	DG Se		st - Rs. 1 la	ics/ Annu	m.				
	=		d capacity	of the DO	3 sets	to he	uced	1. 02 D G	eets of
			0 kVA	01 620 50	3 3013	10 DC	asca	02 D.0	3013 01
		-	of fuel used	l – Diesel	•				
Environmental	1	Construction phase: Rs. 58.87 lacs/ annum							
Management plan	Opera								
Budgetary Allocation	, -		Rs.336.18 Rs.67.53 la						
Traffic Management			ited from t			confli	nent	on 30 m	Parking
	details			ms projec	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	001111		011 50 111	A cer agraria
					Car	Sco	1	Cycle	
	Person P	R	Residential		475	147		1476	
	2		ommercia		321	96		321	
	3	·············	School	`	8	16		64	
	 	Total P	arking Pro	vided	804	245		1861	
			internal re		Widt	h of d	lrive	ways is 6	6 m wide.
			Park	ing effici	encv	stater	neni		
				Prop.	Rec			·	
			Read.	car	ar	- 1			Dwan
			Equiv.	Prkg.	fo	- 1	Į.	rop.	Prop. Equiv.
	Le	Level Car 108. P				op Prk		rkg.	Car
				Frkg. Area		rea m²	Space		
					m ²				
		norms							
	1 1	Stilt/ 30		570			14.54	477	
)	ium					27214.54		47.7
		en	25	101	23:			354.92	28.26
	Base	ment	35	125	87	85	64	172.75	51

3. The proposal has been considered by SEIAA in its 80th meeting & decided to accord environmental clearance to the said project under the provisions of Environment Impact Assessment Notification, 2006 subject to implementation of the following terms and conditions:

General Conditions for Pre- construction phase:-

- (i) This environmental clearance is issued subject to condition that corpus to be built for STP maintenance which shall be separately kept in a separate Bank account to be used solely for maintenance of STP. An agreement shall also be executed with the society for ensuring smooth operation of STP when the maintenance work is handed over to the Cooperative Housing Society
- This environmental clearance is issued sub; a to land use verification. Local authority / planning authority should ensure this with respect to Rules, Regulations, Notifications, Government Resolutions, Circulars. etc. issued if Judgments/orders issued by Hon'ble High Court, Hon'ble NGT, Hon'ble Supreme Court regarding DCR provisions, environmental issues applicable in this matter should be verified. PP should submit exactly the same plans appraised by concern SEAC and SEIAA. If any discrepancy found in the plans submitted or details provided in the above para may be reported to environment department. This environmental clearance issued with respect to the environmental consideration and it does not mean that State Level Impact Assessment Authority (SEIAA) approved the proposed land use.
- (iii) This environmental clearance is issued subject to obtaining NOC from Forestry & Wild life angle including clearance from the standing committee of the National Board for Wild life as if applicable & this environment clearance does not necessarily implies that Forestry & Wild life clearance granted to the project which will be considered separately on merit.
- (iv) Occupation certificate shall be issued to the project only after ensuring availability of drinking water and connectivity of the sewer line to the project site.
- (v) STP capacity shall be increased appropriately considering waste water generation.
- (vi) PP has to abide by the conditions stipulated by SAC & SEIAA.
- (vii) The height, Construction built up area of proposed construction shall be in accordance with the existing FSI/FAR norms of the urban local body & it should ensure the same along with survey number before approving layout plan & before according commencement certificate to proposed work. Plan approving authority should also ensure the zoning permissibility for the proposed project as per the approved development plan of the area.
- (viii) "Consent for Establishment" shall be obtained from Maharashtra Pollution Control Board under Air and Water Act and a copy shall be submitted to the Environment department before start of any construction work at the site.
- (ix) All required sanitary and hygienic measures should be in place before starting construction activities and to be maintained throughout the construction phase.

General Conditions for Construction Phase-

(i) Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche and First Aid Room etc.

- (ii) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal of wastewater and solid wastes generated during the construction phase should be ensured.
- (iii) The solid waste generated should be properly collected and segregated, dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- (iv) Disposal of muck during construction phase should not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (v) Arrangement shall be made that waste water and storm water do not get mixed.
- (vi) All the topsoil excavated during construction activities should be stored for use in horticulture / landscape development within the project site.
- (vii) Additional soil for leveling of the proposed site shall be generated within the sites (to the extent possible) so that natural drainage system of the area is protected and improved.
- (viii) Green Belt Development shall be carried out considering CPCB guidelines including selection of plant species and in consultation with the local DFO/Agriculture Dept.
- (ix) Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- (x) Construction spoils, including bituminous material and other hazardous materials must not be allowed to contaminate watercourses and the dumpsites for such material must be secured so that they should not leach into the ground water.
- (xi) Any hazardous waste generated during construction phase should be disposed off as per applicable rules and norms with necessary approvals of the Maharashtra Pollution Control Board.
- (xii) The diesel generator sets to be used during construction phase should be low sulphur diesel type and should conform to Environments (Protection) Rules prescribed for air and noise emission standards.
- (xiii) The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from concern authority shall be taken.
- (xiv) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- (xv) Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/MPCB.
- (xvi) Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100Km of Thermal Power Stations).
- (xvii) Ready mixed concrete must be used in building construction.
- (xviii) The approval of competent authority shall be obtained for structural safety of the buildings due to any possible earthquake, adequacy of fire fighting equipments etc. as per National Building Code including measures from lighting.
- (xix) Storm water control and its re-use as per CGWB and BIS standards for various applications.

- (xx) Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred
- (xxi) The ground water level and its quality should a monitored regularly in consultation with Ground Water Authority.
- (xxii) The installation of the Sewage Treatment Plant (STP) should be certified by an independent expert and a report in this regard should be submitted to the MPCB and Environmenent department before the project is commissioned for operation. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treated effluent emanating from STP shall be recycled/refused to the maximum extent possible. Discharge of this unused treated affluent, if any should be discharge in the sewer line. Treatment of 100% gray water by decentralized treatment should be done. Necessary measures should be made to mitigate the odour problem from STP.
- (xxiii) Permission to draw ground water and construction of basement if any shall be obtained from the competent Authority prior to construction/operation of the project.
- (xxiv) Separation of gray and black water should be done by the use of dual plumbing line for separation of gray and black water.
- (xxv) Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- (xxvi) Use of glass may be reduced up to 40% to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.
- (xxvii) Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- (xxviii)Energy conservation measures like installation of CFLs /TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible like installing solar street lights, common solar water heaters system. Project proponent should install, after checking feasibility, solar plus hybrid non conventional energy source as source of energy.
- (xxix) Diesel power generating sets proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Use low sulphur diesel. The location of the DG sets may be decided with in consultation with Maharashtra Pollution Control Board.
- (xxx) Noise should be controlled to ensure that it does not exceed the prescribed standards. During nighttime the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.
- (xxxi) Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- (xxxii) Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code, which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air-conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- (xxxiii) The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.

- (xxxiv)Regular supervision of the above and other measures for monitoring should be in place all through the construction phase, so as to avoid disturbance to the surroundings.
- (xxxv) Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.
- (xxxvi)Six monthly monitoring reports should be submitted to the Regional office MoEF, Bhopal with copy to this department and MPCB.

General Conditions for Post-construction/operation phase-

- (i) Project proponent shall ensure completion of STP, MSW disposal facility, green belt development prior to occupation of the buildings. No physical occupation or allotment will be given unless all above said environmental infrastructure is installed and made functional including water requirement in Para 2. Prior certification from appropriate authority shall be obtained.
- (ii) Wet garbage should be treated by Organic Waste Converter and treated waste (manure) should be utilized in the existing premises for gardening. And, no wet garbage will be disposed outside the premises. Local authority should ensure this.
- (iii) Local body should ensure that no occupation certification is issued prior to operation of STP/MSW site etc. with due permission of MPCB.
- (iv) A complete set of all the documents submitted to Department should be forwarded to the Local authority and MPCB.
- (v) In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Department.
- (vi) A separate environment management cell with qualified staff shall be set up for implementation of the stipulated environmental safeguards.
- (vii) Separate funds shall be allocated for implementation of environmental protection measures/EMP along with item-wise breaks-up. These cost shall be included as part of the project cost. The funds earmarked for the environment protection measures shall not be diverted for other purposes and year-wise expenditure should reported to the MPCB & this department.
- (viii) The project management shall advertise at least in two local newspapers widely circulated in the region around the project, one of which shall be in the Marathi language of the local concerned within seven days of issue of this letter, informing that the project has been accorded environmental clearance and copies of clearance letter are available with the Maharashtra Pollution Control Board and may also be seen at Website at http://ec.maharashtra.gov.in.

- (ix) Project management should submit half yearly compliance reports in respect of the stipulated prior environment clearance terms and conditions in hard & soft copies to the MPCB & this department, on 1st June & 1st December of each calendar year.
- (x) A copy of the clearance letter shall be sent by proponent to the concerned Municipal Corporation and the local NGO, if any, from John suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the Company by the proponent.
- (xi) The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM. SO₂, NOx (ambient levels as well as stack emissions) or critical sector parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.
- (xii) The project proponent shall also submit six monthly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB.
- (xiii) The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the Essite of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF by e-mail.
- 4. The environmental clearance is being issued without prejudice to the action initiated under EP Act or any court case pending in the court of law and it does not mean that project proponent has not violated any environmental laws in the past and whatever decision under EP Act or of the Hon'ble court will be binding on the project proponent. Hence this clearance does not give immunity to the project proponent in the case filed against him, if any or action initiated under EP Act.
- 5. In case of submission of false document and non compliance of stipulated conditions, Authority/ Environment Department will revoke or suspend the Environmental Clearance without any intimation and initiate appropriate legal action under Environmental Protection Act, 1986.
- 6. The Environment department reserves the right to add any stringent condition or to revoke the clearance if conditions stipulated are not implemented to the satisfaction of the department or for that matter, for any other administrative reason.
- 7. Validity of Environment Clearance: The environmental clearance accorded shall be valid for a period of 5 years.
- 8. In case of any deviation or alteration in the project proposed from those submitted to this department for clearance, a fresh reference should be made to the department to assess the adequacy of the condition(s) imposed and to incorporate additional environmental protection measures required, if any.
- 9. The above stipulations would be enforced among others under the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986 and rules there under, Hazardous Wastes

(Management and Handling) Rules, 1989 and its amendments, the public Liability Insurance Act, 1991 and its amendments.

10. Any appeal against this environmental clearance shall lie with the National Green Tribunal (Western Zone Bench, Pune), New Administrative Building, 1st Floor, D-, Wing, Opposite Council Hall, Pune, if preferred, within 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

(Ajoy) Mehta)
Principal Secretary,
Environment department &
MS, SEIAA

Copy to:

- 1. Shri. R. C. Joshi, IAS (Retd.), Chairman, SEIAA, Flat No. 26, Belvedere, Bhulabhai desai road, Breach candy, Mumbai- 400026.
- 2. Shri. Jagdish Joshi, Chairman, SEAC-III, 3 Tahiti CHS Juhu- Versova Link Road, Andheri (W), Mumbai- 400.
- 3. Additional Secretary, MoEF & CC, Indira Paryavaran Bhavan, Jorbagh Road, Aliganj, New Delhi-110003.
- 4. Member Secretary, Maharashtra Pollution Control Board, with request to display a copy of the clearance.
- The CCF, Regional Office, Ministry of Environment and Forest (Regional Office, Western Region, Kendriya Paryavaran Bhavan, Link Road No- 3, E-5, Ravi-Shankar Nagar, Bhopal- 462 016). (MP).
- 6. Regional Office, MPCB, Pune.
- 7. Collector, Pune
- 8. Commissioner, Municipal Corporation, Pune.
- 9. IA- Division, Monitoring Cell, MoEF & CC, Indira Paryavaran Bhavan, Jorbagh Road, Aliganj, New Delhi-110003.
- 10. Select file (TC-3)

(EC uploaded on 2/3/2015

